



ECL-557HIM

ECL-557HIM Varifocal Lens & Auto-Iris Camera

This indoor/outdoor dome incorporates tamper resistant features, an anti-ergonomic design that discourages casual vandalism, and can be aimed in almost any direction. 30 infrared LEDs turn on when light reaches a pre-set threshold, allowing operation in total darkness. A mechanical IR filter enhances video quality under all conditions.



120° Vertical Camera Angle Adjustment



360° Horizontal Camera Angle Adjustment



90° Lens Angle Adjustment

Vandal & Tamper Resistant

Constructed with public placement in mind, this camera has several features making it difficult to vandalize or disable.

Conical base is hard to grip and is made of hardened aluminum.

Screws on base require a special tool.

Polycarbonate dome is designed to withstand impacts and hard blows.

Deterrent LED - White strobing LED flashes periodically to indicate camera location and power-on status. Use it to deter criminal activity and increase business awareness. User can disable this feature if not desired.



Flexible Mount and Route

Mount at any angle and route your video and power cords either through the base or use the external access portal. Use a metal conduit for added security.

Threaded portal provides protected access point.



Adjustable IR Control

Switchable setting to control IR delay from 5 seconds to 15 seconds to account for variable light conditions such as shadows, clouds, or other unpredictable concerns.



General Specifications

Video Sensor: 1/3" Sony HQ1 Infrared Sensitive CCD
of Pixels: NTSC - 768(h) x 494(v) PAL - 752(h) x 582(v)
Horizontal Resolution: 540 TV lines
Scanning System: 2:1 Interlace
Light Level Sensitivity: 0.5 Lux (day) / F1.2, (0.0 Lux w/IR on)
Video Signal Synchronization: Internal
Video Signal Level: 1Vp-p, 75 Ohm impedance
IR LED Array: 30 Units Operating at 850nm Wavelength
Deterrent LED: White LED, flashes approx. every 2 seconds
Signal to Noise Ratio: >48dB
Gamma Correction: 0.45
Auto-White Balance: Multi-Color Temperature AWB
Gain Control: Full Auto-Gain Control (AGC)
Back Light Compensation: Full Auto BLC
Aperture Correction: 2H mode of H.V
Electronic Shutter: Auto, up to 1/100,000 sec.
Dual Power Capable: 12VDC or 24VAC (installers choice) 300mA (nominal), 600mA with IR on

Optical Specifications

Lens: 3.8-9.5mm varifocal, auto iris
Mechanical IR filter

Environmental Specifications

Operating Temperature: -10 degrees to +45 degrees (C) 14 degrees to +113 degrees (F)
Storage Temperature: -30 degrees to +60 degrees (C) -22 degrees to +140 degrees (F)

Physical Specifications

Dim.: 157mm x 96mm (6.18" x 3.78")
Weight: 630.5g (1.39lbs)

Suggested Uses:

Public transit, boardwalks, malls, lobbies, theaters, strip malls, trains, town squares, window displays, classrooms, security centers, controlled access rooms, factory floors, cafeterias, kitchens, sports arenas, arcades, playgrounds, taverns, restaurants, carnivals, bus stops, food prep areas, exit doors, ticket booths, party stores, kwiikee marts, checkout lines, customer service desks, teller counters, any kind of waiting area open to the public.