

ECL-SP570 Color High Speed Dome

Fully Integrated Indoor and Outdoor Enclosures with Camera and Zoom Lens

The ECL-SP570 High Speed Dome combines the essential industry standards in a small, easy to operate platform. The dome is equipped with all the features necessary to meet the requirements of even the most demanding customers. Its compact and feature rich design allows discrete placement in aesthetic architectural environments while providing outstanding performance. Overall, the SP570 provides enhanced productivity with unlimited possibilities for commercial and industrial applications.

Key Features

- Full Sony Solution
- Full Automatic Day/Night Filter
- Video Pattern Recording
- Better Sensitivity & Faster Zoom
- 360° Continuous Rotation
- 128 Programmable Presets
- 18X Optical & 12X Digital Zoom
- Faster & More Accurate Auto Focus
- Compatible with Most DVR's
- Speed up to 400° per Second

Indoor Wall Mount

ECL-SP570



Outdoor Wall Mount



<p>ECL-SP570 (default) Indoor Speed Dome with Indoor Wall Mount</p>	<p>ECL-SP570P Indoor Speed Dome with 3in Indoor Pendant Mount</p> <p>ECL-SP570P2 Indoor Speed Dome with 9in Indoor Pendant Mount</p>	<p>ECL-SP570E Outdoor Speed Dome with Outdoor Wall Mount</p>	<p>ECL-SP570EP Outdoor Speed Dome with 3in Outdoor Pendant Mount</p> <p>ECL-SP570EP2 Outdoor Speed Dome with 9in Outdoor Pendant Mount</p>
--	--	---	--

ECL-SP570 Color High Speed Dome


Fully Integrated Indoor and Outdoor Enclosures with Camera and Zoom Lens



Indoor







Outdoor



Day Night Operation	Color During Day, B/W at Night (Auto Switching)
Pick Up Device	1/4" Sony Super HAD EX-View CCD
Resolution	480 TV Lines
Minimum Illumination	0.7 Lux
Lens	4.1 - 73.8mm Auto Focus (F1.4 - F3.0)
Zoom	18X Optical, 12X Digital (216X Total)
Infra-Red Sensitivity	None (IR Block Filter)
Vertical Sync	Internal
Gain Control	Electronic Shutter 1/1 - 1/10,000sec. (22 steps)
White Balance	Auto, ATW, Indoor, Outdoor, One Push, Manual

Horizontal Rotation	(Pan Travel) 360° Continuous
Vertical Rotation	(Tilt Travel) 0° - 90° (Auto Flip)
Protocols	(RS-485) Pelco, Pelco-D, Pelco-P, Eclipse, Ultrak
Speed	400° Per Second
Speed Control	Variable (Adjusts to Manipulation)
Presets	128 Programmable
Touring (Auto Scan)	3 Speed Selectable
Smart Scan	2 Positions Preset (Adjustable Speed)
Focus Control	Manual / Auto (sensitivity adjustment normal or low)
Pan/Tilt Accuracy	+/- 0.05° Preset Recall
Upper Dome Material	Aluminum (IP66 for Outdoor Enclosure)
Lower Dome Material	Clear Acrylic (other options available)
Power Source	24 VAC (30 Watts)
Temperature	0 - 122F (-14 - 122F with Heater)
Humidity	0 - 85% RH Non Condensing

ECL-SP570 Mounting Bracket Options

<p>Indoor Wall Mount</p> 	<p>3 or 9in Indoor Pendant Mount</p> 	<p>Outdoor Wall Mount</p> 	<p>3 or 9in Outdoor Pendant Mount</p> 
--	--	--	---