

2 Megapixel HD IP Surveillance Camera

This professional surveillance camera is for use indoors or outdoors and is vandal resistant. Built-in IR illumination for 98 ft.



Key Features:

Advanced Imaging Options

- Wide-angle fixed lens - 3.6mm std (6.0mm or 12.0mm optional)
- Wide Dynamic Range
- Smart IR (30m 98ft)

Advanced Mechanical Design

- Wide temperature range [-31F to 140F]
- IP66 weather resistant

Advanced Functionality

- 16:9 or 9:16 aspect ratio [Perfect for corridors]
- Triple streaming
- ONVIF conformance
- Remote access (PC, iOS, Android)
- 4KV surge protection on network interface

Specifications:

Camera			
Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS		
Lens	3.6mm@F1.8 Angle of view(H): 85°	6.0mm@F1.8 Angle of view(H): 53°	12.0mm@F1.8 Angle of view(H): 27°
Shutter	Auto/Manual, 1/6~1/8000 s		
Min. Illumination	Color: 0.02 Lux (F1.8, AGC ON) 0 Lux with IR on		
Day/Night	IR-cut filter with auto switch (ICR)		
IR Range	Up to 30m (98 ft) IR range		
S/N	>52dB		
WDR	Digital		
Noise Reduction	2D/3D		
Video			
Max. Resolution	1920×1080		
Video Compression	H.264/MJPEG		
Frame Rate	1080P (1920*1080): Max. 30 fps; 720P (1280*720): Max. 30 fps; D1 (720*576): Max. 25 fps		
Video Streaming	Triple		
9:16 Corridor Mode	Supported		
ROI	Supported		
OSD	Up to 8 OSDs		
Motion Detection	Up to 2 areas		
Privacy Mask	Up to 4 areas		
Network			
Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SNMP, SIP, QoS		
Compatible Integration	ONVIF, API		
Interface			
Network	1 RJ45 10M/100M Base-TX Ethernet		
General			
Power	12 V DC, or PoE (IEEE802.3 af) Power consumption: Max 6.4 W		
Dimensions (L × W × H)	157.3 × 62.4 × 63 mm (6.2" × 2.5" × 2.5")		
Weight	0.45 kg (0.99 lb)		
Working Environment	-35°C ~ +60°C (-31°F ~ 140°F), Humidity ≤ 95% RH(non-condensing)		
Ingress Protection	IP66		