



**HARD ALLOY
ANTI-VANDAL
CASE**

INCREASE SAFETY

- Faster access to secure areas

OUTDOOR DESIGN

- Weatherproof Design

EXTERNAL PROGRAMMING KEYPAD

ECL-ACC890K
Programming Keypad
Sold Separately



Includes electric door relay, ECL-ACC899



0.75"



Threaded Security Screw Port

Keypad Port

2.0"



Attached cable not shown for clarity.

Easy to install. Easy to program.
Easy to REPROGRAM at any time
using the secure Programming Keypad, ECL-ACC890K

MODEL	ECL-ACC890
CONSTRUCTION	Hardened zinc-alloy
READ RANGE	10-18cm (at 125kHz operation)
TIME ZONES	11, user defined in client software
HOLIDAY SCHEDULING	User defined in client software
USERS	1024 in Networking mode, 65536 in Standalone mode
AUTO-OPEN DOOR ZONES	Two (programmable)
ALARM OUT	Function Supported using Auxiliary Relay (optional)
COMMUNICATION	RS485
BAUD RATE	Baud Rate: 9600 bps (N, 8, 1)
DOOR RELAY TIME	0, 0.1-600 sec.
ALARM RELAY TIME	0, 1-600 sec.
TAMPER RESISTANCE	Limit switch (Form C)
AUXILIARY WG PORT	WG 26/34, ABA II
SERIAL OUT	TTL (4800 bps, N, 8, 1)
WEATHERPROOF RATING	IP54, good for indoor or outdoor placement
REAL TIME CLOCK	YES
INDICATORS	LED and Beeper
POWER	12VDC
DIMENSIONS	6 1/8" x 2" x 3/4" thick
WEIGHT	290g (10.23oz)
OPERATING TEMPERATURE	-20°C to +75°C (-4°F to +167°F)

Visit EclipseCCTV.com
for all of your
surveillance & security
product needs.