



ECL-AD88VW
IP66

KEY FEATURES

- AHD lossless video output
- 1080P real time image, high resolution
- CMOS Progressive scan perfectly capture the moving object
- 30-35m IR night viewing distance
- Switch between AHD and Analog signal through OSD

MODEL: ECL-AD88V SERIES

SPECIFICATIONS

* GENERAL	
Operating Environment	-20 °C ~ + 50 °C 10 ~ 90% humidity
Power Supply	DC12V
Power Consumption	< 4.2W
Water-proof	IP66
Max. Transmission Distance	500M by Coaxial or CAT5 cable
Certifications	CE, RoHS, ISO9001

* CAMERA	
Sensor	1/2.8" Sony
Effective Pixels	1930 (H) x 1088 (V)
Video Frame Rate	1080P@25/30fps
Image System	PAL / NTSC
Frame Rate	30 fps (60 Hz), 25fps (50 Hz)
Image Size	1080P (1920 x 1080)
Video output	AHD/Analog
Mini-illumination	0 Lux when IR on
OSD	Yes
Lens	2.8-12mm lens
IR range	20m
IR Leds	36pcs φ5mm IR Leds
* FUNCTION	
Day/Night	Built-in ICR filter
S/N Ratio	More than 50db(AGC Off)
Electronic Shutter	1/60s ~ 1/67500s
White Balance	Auto
DNR	Yes
AGC	Auto



ECL-AD88VB



ECL 160314 118 V2 ENG

Copyright © 2016 CCTV Outlet Corp. ALL RIGHTS RESERVED. Information and data contained in this spec sheet are for general reference only and may change at any time.